

**DECLARATION OF PERFORMANCE**  
according to Annex III of Regulation (EU) No. 305/2011  
amended by Delegated Regulation (EU) No. 574/2014

Nr. J 232

**1. Product type unique identifier code:**

KÖSTER Joint Sealant FS-H (black)

**2. Intended use:**

Cold applied Joint Sealant for use on streets, parking decks, bridge decks, airfields and other trafficked areas

**3. Manufacturer:**

KÖSTER BAUCHEMIE AG  
Dieselstraße 1 - 10  
26607 Aurich

**4. Systems for assessment and verification of performance:**

System 4

**5. Harmonized Norm:**

EN 14188-2

**6. Notified bodies:**

Not relevant

**7. Declared performance:**

Main features	Performance	System for assessment and verification of consistency of performance	Harmonized technical specification
Adhesion and stretching ability	Tensile modulus at 100% elongation: at 23 °C ≥ 0.15 MPa at -20 °C ≤ 0.6 MPa	System 4	EN 28340
Adhesion	No failure at -20 °C ≤ 0.6 MPa		EN ISO 9047
Waterproof	Resilience ≥ 70%		EN ISO 7389
	Volume loss ≤ 5%		EN ISO 10563
Resistance to deformation	Resilience ≥ 70%		EN ISO 7389
	Volume loss ≤ 5%		EN ISO 10563
Durability of waterproofing against chemical attack	Passed		EN 14184-4
Durability of all mandated properties against aging	Change in tensile modulus at 100% elongation ≤ ± 20%		EN 14187-8
Resistance to flame	Passed	EN 14187-7	

The performance of the product according to numbers 1 and 2 corresponds to the declared performance according to number 7. The manufacturer according to number 3 is solely responsible for the preparation of this declaration of performance.

Signed for and on behalf of the manufacturer by:

Dr. Eike Kunst  
(Research and development Export)



...10.01.2023.....  
(Place and date of issue)

.....  
(Signature)